


## FEATURES


- | High Current Capability
- | Low Forward Voltage Drop



SOD-123

## MECHANICAL DATA

- | SOD-123 Small Outline Plastic Package
- | Polarity: Color band denotes cathode end
- | Mounting Position: Any



Schematic Symbol

## APPROVALS

<b>RoHS</b>	Compliance with 2011/65/EU
<b>HF</b>	Compliance with IEC61249-2-21:2003



## MAXIMUM RATINGS ( $T_A=25^{\circ}\text{C}$ )



Parameter	Symbol	B5817W	B5818W	B5819W	Unit
Marking		SJ	SK	SL	
Peak Repetitive Reverse Voltage	$V_{RRM}$	20	30	40	V
RMS Reverse Voltage	$V_{R(RMS)}$	14	21	28	V
Maximum DC blocking voltage	$V_{DC}$	20	30	40	V
Maximum average forward rectified current	$I_{FM}$	1.0			A
Peak forward surge current 8.3 ms single half sine-wave	$I_{FSM}$	25			A
Power Dissipation	$P_D$	500			mW
typical thermal resistance	$R_{\theta JA}$	250			$^{\circ}\text{C}/\text{W}$
Operating junction temperature	$T_J$	125			$^{\circ}\text{C}$
Storage temperature range	$T_{STG}$	-50+150			$^{\circ}\text{C}$

## ELECTRICAL CHARACTERISTICS( $T_A=25^{\circ}\text{C}$ )

Parameter		Symbol	Test Conditions	B5817W	B5818W	B5819W	Unit
Maximum forward voltage		$V_F$	$I_F=1.0\text{A}$	0.450	0.550	0.600	V
			$I_F=3.0\text{A}$	0.750	0.875	0.900	V
Reverse breakdown voltage		$V_R$	$I_R=1\text{mA}$	20	30	40	V
Reverse Leakage Current	B5817W	$I_R$	$V_R=20\text{V}$	1.0			mA
	B5818W		$V_R=30\text{V}$	1.0			mA
	B5819W		$V_R=40\text{V}$	1.0			mA
Type junction capacitance		$C_j$	$V_R=4.0\text{V}, f=1\text{MHz}$	120			pF


## CHARACTERISTIC CURVES




**Fig.3 Capacitance Characteristics**

**Fig.4 Power Derating Curve**


## SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ( $T_{s(min)}$ )	150°C
	Temperature Max ( $T_{s(max)}$ )	200°C
	Time (min to max) ( $t_s$ )	60 – 180 secs
Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak)		3°C/second max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/second max
Reflow	Temperature ( $T_L$ ) (Liquidus)	217°C
	Time (min to max) ( $t_L$ )	60 – 150 seconds
Peak Temperature ( $T_p$ )		260°C
Time within 5°C of actual peak Temperature ( $t_p$ )		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature ( $T_p$ )		8 minutes max.
Do not exceed		260°C




## SOD-123 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.60	2.80	0.102	0.110
B	1.50	1.70	0.059	0.067
C	3.55	3.85	0.140	0.152
D	1.05	1.25	0.041	0.049
E	0.45	0.65	0.018	0.026
F	0.08	0.15	0.003	0.006
H	0.00	0.10	0.000	0.004
L	0.25	0.45	0.010	0.018

## RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.00	4.30	0.157	0.169
B	0.75	0.85	0.030	0.033
C	0.95	1.05	0.037	0.041

## ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
B5817W-B5819W	SOD-123	3000PCS	7"

To find your local partner within Semiwell's website : [www.semiwell.com.cn](http://www.semiwell.com.cn)

© 2023 Semiwell Microelectronics Co.,Ltd.

The content of this document has been carefully checked and understood. However, neither Semiwell nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiwell does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiwell. Latest publications and a complete disclaimer can be downloaded from the Semiwell website. All trademarks recognized.