

FEATURES

- | High Current Rectifier Schottky Diode with Low VF Drop
- | Low Voltage ,Low Inductance
- | For Power Supply
- | For Detection and Step-up-Conversion



SOD-323

MECHANICAL DATA

- | Encapsulation: SOD-323 Small Outline Plastic Package
- | Polarity: Color band denotes cathode end
- | Mounting Position: Any



Marking



Schematic Symbol

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS (T_A=25°C)

Parameter	Symbol	Value	Unit
DC Blocking voltage	V _R	10	V
Forward current	I _F	3	A
Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	5	A
Typical thermal resistance	R _{θJA}	286	°C/W
Power Dissipation	P _D	350	mW
Operating junction range	T _J	125	°C
storage temperature range	T _{STG}	-65 to 150	°C

ELECTRICAL CHARACTERISTICS($T_A=25^\circ\text{C}$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	$I_F=100\text{mA}$		0.33	0.38	V
		$I_F=500\text{mA}$		0.41	0.50	V
		$I_F=1000\text{mA}$		0.45	0.60	V
Reverse breakdown voltage	$V_{(BR)}$	$I_R=1\text{mA}$	10			V
Maximum reverse current $T_J=25^\circ\text{C}$	I_R	$V_R=5\text{V}$			15	μA
		$V_R=8\text{V}$			25	μA
Total capacitance	C_{tot}	$V_R = 5.0\text{V}, f = 1\text{MHz}$		30		pF

CHARACTERISTIC CURVES






Fig.1 Forward Characteristics

Fig.2 Reverse Characteristics



Fig.3 Capacitance Characteristics

Fig.4 Power Derating Curve


SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(\min)}$)	150 $^\circ\text{C}$
	Temperature Max ($T_{s(\max)}$)	200 $^\circ\text{C}$
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3 $^\circ\text{C}/\text{second}$ max
$T_{s(\max)}$ to T_L - Ramp-up Rate		3 $^\circ\text{C}/\text{second}$ max
Reflow	Temperature (T_L) (Liquidus)	217 $^\circ\text{C}$
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260 $^\circ\text{C}$
Time within 5 $^\circ\text{C}$ of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6 $^\circ\text{C}/\text{second}$ max
Time 25 $^\circ\text{C}$ to peak Temperature (T_p)		8 minutes max.
Do not exceed		260 $^\circ\text{C}$




SOD-323 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.60	1.90	0.063	0.075
B	1.15	1.45	0.045	0.057
C	2.39	2.70	0.094	0.106
D	0.80	1.10	0.031	0.042
E	0.25	0.40	0.010	0.016
F	0.10	0.20	0.004	0.008
H	-	0.10	-	0.004
L	0.20	-	0.008	-

RECOMMENDED PAD LAYOUT DIMENSIONS



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.87	3.12	0.113	0.123
B	0.66	0.91	0.026	0.036
C	0.66	0.91	0.026	0.036

ORDERING INFORMATION

Part Number	Component Package	QTY/Reel	Reel Size
BAT60B	SOD-323	3000PCS	7"

To find your local partner within Semiwell's website : www.semiwell.com.cn

© 2023 Semiwell Microelectronics Co.,Ltd.

The content of this document has been carefully checked and understood. However, neither Semiwell nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiwell does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiwell. Latest publications and a complete disclaimer can be downloaded from the Semiwell website. All trademarks recognized.